

Digital Cameras (USB 2.0) and Lens

- 86-0240 uEye 1240 LE-C, 0.55in, CMOS, 25fps, 1280x1024, 1.3MP, SXGA, C-Mount digital USB color camera
- 86-0274 uEye 1460-C, 0.5in, CMOS, 11fps, 2048x1536, 3.1MP, QXGA, C-mount digital USB color camera
- 86-0270 uEye 1460LE-C, 0.5in, CMOS, 11fps, 2048x1536, 3.1MP, QXGA, C-mount digital USB color camera
- 86-10004 uEye 1480-C, 0.5in, CMOS, 5-6fps, 2560x1920, 5MP, QSXGA, C-mount digital USB color camera
- 86-10005 uEye 1490-C, 0.5in, CMOS, 3fps, 3840x2748, 10MP, QHDTV, C-mount digital USB color camera
- 86-0278 uEye 2240-C, 0.5in, CCD, 30fps, 1280x1024, 1.31MP, SXGA, Cmount digital USB color camera
- 86-0280 uEye 2250-C, 0.55in, CCD, 15fps, 1600x1200, 1.92MP, UXGA, C-mount digital USB color camera



Motorized stage and focus packages

Compatible only with OmniMet™ Capture Basic version 9.0 and higher:

- 86-10003 Motorized stage and focus drive for Nikon MA200
- 86-5435 Motorized stage and focus drive for Nikon Eclipse ME600 and L150, 100mm x 100mm stage scan size

Monitors

- 85-0124 24in Monitor, LCD with 1920 x 1200 display capability
- 85-0127 27in Monitor, LCD with 2650 x 1600 display capability

